



GUIDE FOR THE MAINTENANCE OF EVOLUTION DESIGN RESILIENT FLOORING

The Evolution range floors have a polyurethane treatment that protects the surfaces, reducing the need for cleaning cited in the maintenance regime, with consequent advantages in terms of costs and environmental protection. The instructions of maintenance reported below are designed to minimize costs without in the long term compromise the aesthetic appearance of the floor.

Once completed the installation, (if glued you must not step on the floor for 24 hours until the glue has not dried) proceed in this way:

- If glued remove debris and make sure that all of dried glue has been removed from the floor surface;
- Sweep or pass the floor with vacuum cleaner to remove dust and debris;
- Pass on the floor with a rag wet microfiber and a low foaming cleaner (detergent G).

The recommendations given below serve as guidelines and the frequency of cleaning operations can be changed to optimize the appearance of the floor.

Daily operations

- Sweep or pass the floor with a vacuum cleaner to remove dust and dirt.
- If necessary, remove tracks and resistant stains with a low-foaming alkaline cleaner (detergent G).

Weekly/ monthly operations

- Sweep or pass the floor with a vacuum cleaner to remove dust and dirt.
- If necessary, the glued products can be cleaned with a scrubber equipped with special bearings and a low foam alkaline detergent. If you do not have a device, pass on the floor with a rag in a damp microfiber and a low foam alkaline detergent (cleaning agent G).



CLEANING WITH AUTO SCRUBBER, ROTOCLEANER OR SINGLE -BRUSH MACHINE

Caution:

Make sure that the machine is used efficiently and immediately removes water and detergent.

Periodic cleaning (1 time per week):

- Use discs for normal maintenance type 3M red.
- Neutral detergent suitable for PVC floors, alkaline low foam suitable for the thorough cleaning of the "cleaner G type floors".
- Do not use abrasive disks or any procedure that risks damaging the surface (PU surface).

REMOVING / CLEANING DIFFICULT STAINS

Paints:

- Do not use abrasive sponges or steel wool, use specific solvent to paint if it is known. After removing the stain, rinse well with water.

Acrylic Adhesives:

- Apply water with detergent, leave for a few minutes and then remove. If the stain persists apply pure detergent, leave for a few minutes and then rinse.

Rubber marks / shoes:

- Apply pure detergent, leave it on for five minutes, scrub, rinse with plenty of water.